

We are pleased to offer Indonesia steam coal

Price : FOB gearless panamax

Remark : The offer is subject to our final confirmation.

1. Coal Spec : 4500GAR (4170 NAR), 30% TM, 0.35% Sulfur (1% Max), 6% Ash, HGI 50

2. Quantity : 65kt (+/- 10% vessel option), Gearless vessel.

3. Shipment : TBA

4. Price : one FOB fixed price can be offer as per your interest.

5. Loading rate : 15,000mt/day PWWD SHINC, load port is Adang bay.

SPEC as below

4500 kcal/kg ARB (Under ASTM-Standard)

Coal Specification of				Typical	Min/Max
Proximate Analysis	Total Moisture	ADB	%wt	30.0	
	Inherent Moisture		%wt	20.0	
	Ash		%wt	6.0	
	Volatile Matter		%wt	38.0	
	Total Sulphur		%wt	0.35	1.0
Heating Value		ARB	kcal/kg	4,500	4,350
Ultimate Analysis	Carbon	DAFB	%wt	65.0	
	Hydrogen		%wt	5.2	
	Nitrogen		%wt	1.0	
	Oxygen		%wt	28.3	
	Sulphur		%wt	0.5	
HGI (Hard Grove Index)				50	45
SIZE	0 x 50 mm		%	100.0	95.0
	0 x 2 mm		%	25.0	30.0
AFT (Reducing)	Initial			1,180	1,150
	Hemispherical			1,250	1,200
	Fluid			1,300	1,250
Ash Analysis	SiO2	DB	%wt	37.0	

	Al2O3		%wt	24.5	
	Fe2O3		%wt	22.0	
	CaO		%wt	6.5	
	MgO		%wt	1.2	
	Na2O		%wt	0.2	
	K2O		%wt	1.3	
	Mn3O4		%wt	0.2	
	TiO2		%wt	1.7	
	SO3		%wt	4.2	
	P2O5		%wt	0.3	
	Others		%wt	0.9	