Coach Bus

TECHNICAL SPECIFICATIONS

Dimensions		
Overall Length	7480 1	mm
Overall Width	2360 1	mm
Overall Height	2950 1	mm
Wheel Base	3800 ı	mm
Front Overhang	1280 ı	mm
Rear Overhang	24001	mm
Interior Height	1900 ı	mm
First Step Height	380 ı	nm
Gross Vehicle Weigh	ht 7850	kg
Seats Capacity	24	-31
Luggage Compartme	ent Volume* 2.1	m3
Engine		
Engine Model	YC4D130-45	
Engine Type	4 cylinders in-line,4 stroke, water cooling	
Position/Fuel	Front/Disel	
Max Torque	500 N.M	
Max Output	103 kw	
Displacement	4752 ML	
Emission Standard	Euro IV	
Chassis		
Chassis Model	EQ6690K4AC/Dongfeng	
Gear box	DF5S550	
Clutch	Single plate, dry f friction, diaphragm spring, air booster	•
Front Axle	Dongfeng stock(3T)	
Rear Axles	Dongfeng stock (5T)	
Suspension	Leaf spring suspension front 9 rear 11	
Steering	Power steering	
Brakes	Dual circuit air br rake	
Fuel Tank	135L	
Tyres	8.25-16	
•	8.25R16, 7.50-20, 7.50R20	
Parking Brake	Spring actuated parking brake	
Battery	6-QW-120DF/28V 70A	
Others	Copper water tank ,exhaust brake	
Body	,	
Body Type	Semi-integral body construction	
Interior Trimming	Air condition bus's interior,	
8	Double inner luggage rack	
door&door pump	Front set pneumatic folding passenger door	
Side Window	the side window:top:splice,bottom:push-pull.	
windscreen	Front : laminated glass; Rear : toughened glass	
Defroster	Defroster with changeable power 24V \ 170W	
Windscreen Wiper	opposed electric wiper system	
Rear reflecting	Rabbit ears rearview mirror, general inner rearview mir	or
Seats	2+2,25 general seats	
D. instinue	DI :	

Pneumatic outer swinging door

Painting

Optional

Shock-abosorbing seat for driver, Luxurious adjustable armest seat

Plain paint

Photo



Safety & Performance

Standard

GPS System, vehicle travelling data recorder Speed-limiting device (100km/h top)

Safety belt equipped with every seat

2 safety hammer, one 2kg Fire Extinguisher, side curtain

Steel plate stamping hatch

Half front window rolled sun visor

Flat floor with non-sunk back

700 Skylight, PVC floor, air horn

Optional

Dongfeng Pannico top-mounted A/C 16KW,PN40 compressor Folding side curtain,front window rolled sun visor,corridor carpet High and low,quatz sand floor,aluminum pattern floor or Iron

wood floor or Iron pattern floor

Electronically controlled rearview mirrors

7-inch color screen reversing rearview monitoring system

Commode handle, sunk back luggage tank

Metallic paint

ABS (Antilock Braking System)

Independent fuel heater YT-Q16.3R(3 radiator);

Entertainment Systems & Digital Amenities

Standard

MP3 radio system

Electric clock with temperature display

Outer swinging door remote switch controller

Combination lamps for both front and back

Combination lamps for both front and back

Optional

MP4/MP5 video system; ventilation Skylight,type cover side luggage tank,water dispenser,Black headlight

Off monitoring system, In-bus video monitoring system (7 inch color scree, card reader or disk, The camera is no more than 4), electronic bus-stop annunciator, money collection box (manual or electric), Fire extinguisher (4kg), ventilation skylight